

HEIDENHAIN



Product Information

LIC 4100 Absolute Exposed Linear Encoders

11/2023

LIC 4113, LIC 4133, LIC 4193

Absolute linear encoders for measuring lengths of up to 3 m

- For measuring steps of down to 1 nm
- · Glass or glass ceramic measuring standard
- Measuring standard secured with adhesive film or fixing clamps
- Consisting of a linear scale and scanning head (with straight or angled cable outlet)

• Version available for use in a high vacuum (see separate Product Information document)



6 = Direction of motion of the scanning unit

for increasing position values

Scale	LIC 4003								
Measuring standard Coefficient of linear expansion*	METALLUR gra $\alpha_{\text{therm}} \approx 8 \cdot 10^{-6}$ $\alpha_{\text{therm}} = (0 \pm 0.5)^{-6}$	METALLUR grating on glass or glass ceramic $\alpha_{\text{therm}} \approx 8 \cdot 10^{-6} \text{ K}^{-1}$ (glass) $\alpha_{\text{therm}} = (0\pm0.5) \cdot 10^{-6} \text{ K}^{-1}$ (Robax glass ceramic)							
Accuracy grade*	$\pm 1 \ \mu m$ (only for	±1 μm (only for Robax glass ceramic), ±3 μm, ±5 μm							
Baseline error	≤ ±0.275 µm/10) mm							
Measuring length (ML)* in mm	240 340 2640 2840 3	440 640 84 3040 (Robax glass	40 1040 12 s ceramic only	240 1440 up to ML of	1640 1840 1640)	2040 2240	2440		
Mass	3 g + 0.11 g/mn	n of measuring le	ngth						
Scanning head	LIC 411	LIC 413	LIC 419F	LIC 419M		LIC 419P	LIC 419Y		
Interface	EnDat 2.2	EnDat 3	Fanuc Serial Interface αiMitsubishi high speed interfacePanasonic Serial InterfaceYaskawa Serial Interface						
Ordering designation*	EnDat22	E30-RB E30-R4	Fanuc05	Mit03-4	Mit03-2	Pana02	YEC07		
Measuring step ^{*1)}	10 nm, 5 nm, 1 nm 10 nm, 5 nm, 1 nm 11 nm								
Calculation time t _{cal} Clock frequency	≤ 5 μs ≤ 16 MHz								
Traversing speed ²⁾	≤ 600 m/min	≤ 600 m/min							
Interpolation error	±20 nm								
Electrical connection*	Cable (1 m or 3 15-pin D-sub co 4-pin MINI-SNA	m) with 8-pin M1 nnector (male) (fc P connector (mal	2 coupling (m or all interfaces e) (EnDat 3:E3	ale) (for all int s; EnDat 3: E3 30-R4)	terfaces; EnDa 30-RB), or	it 3: E30-RB),			
Cable length (with HEIDENHAIN cable)	≤ 100 m		≤ 50 m	≤ 30 m		≤ 50 m			
Supply voltage	DC 3.6 V to 14 \	/							
Power consumption ²⁾ (max.)	<i>At 3.6 V:</i> ≤ 700 mW <i>At 14 V:</i> ≤ 800 mW	At 3.6 V: ≤ 85 At 14 V: ≤ 95	0 mW 0 mW						
Current consumption (typical)	<i>At 5 V:</i> 75 mA (without load)	At 12 V: 35 mA (without load)	<i>At 5 V:</i> 95 m.	A (without loa	ad)				
Vibration 55 Hz to 2000 Hz Shock 6 ms	\leq 500 m/s ² (El \leq 1000 m/s ² (El	N 60068-2-6) N 60068-2-27)	1						
Operating temperature	–10 °C to 70 °C								
Mass	Scanning head: Cable: Connectors:	Scanning head:≤ 18 g (without cable)Cable:M12 coupling and D-sub connector: 20 g/m; MINI-SNAP connector: 15 g/mConnectors:M12 coupling: 15 g; D-sub connector: 32 g; MINI-SNAP: 8 g							
* Please select when ordering ¹⁾ <i>Mitsubishi:</i> ML ≤ 2040 mm / <i>Yaskawa:</i> ML ≤ 1840 mm ²⁾ See <i>General electrical information</i> in the <i>Interfaces of HEIDENHAIN Encoders</i> brochure									

Robax is a registered trademark of Schott-Glaswerke, Mainz, Germany Product Information: LIC 4100 11/2023

Vacuum Ø 3.5 mm > 10 mm ≥ 50 mm

Product Information: LIC 4100

Ø 2.9 mm > 6 mm ≥ 30 mm

11/2023

PUR

		* ^	~	
		LIC 4100		
4 X 47 023 252 R9	HEIDENHAIN METALLUR	HEIDENHAIN www.heidenhein.de		

LIC 4115, LIC 4135, LIC 4195

Absolute linear encoders for measuring lengths of up to 28 m

- For measuring steps of down to 1 nm
- Steel scale tape pulled through aluminum extrusions and tensioned
- Consisting of a linear scale and scanning head (with straight or angled cable outlet)



ML > 2040 (e.g., 5040)





Product Information: LIC 4100

11/2023

Scale	LIC 4005							
Measuring standard Coefficient of linear expansion*	Steel scale tape Depends on the	with absolute an mounting surfac	id incremental e	METALLUR	track			
Accuracy grade*	±5 µm							
Baseline error	≤ ±0.750 µm/50) mm (typical)						
Measuring length (ML)* in mm	140 240 1540 1640 1	340 440 54 740 1840 194	40 640 7 40 2040	740 840	940 1040	1140 1240	1340 1440	
	Greater MLs (up	Greater MLs (up to 28440 mm) with a single-section scale tape and individual scale carrier sections						
Mass	Scale tape: 31 g	ı/m; assembly pai	rts: 80 g + n ¹⁾	· 27 g; scale	tape carrier: 1	87 g/m		
Scanning head	LIC 411	LIC 413	LIC 419F	LIC 419M		LIC 419P	LIC 419Y	
Interface	EnDat 2.2	EnDat 3	Fanuc SerialMitsubishi high speedPanasonicYaskawaInterface αiinterfaceSerialSerialSerialInterfaceInterfaceInterfaceInterfaceInterface					
Ordering designation*	EnDat22	E30-RB E30-R4	Fanuc05	Mit03-4	Mit03-2	Pana02	YEC07	
Measuring step* ²⁾	10 nm, 5 nm, 1 nm 10 nm, 5 nm, 1 nm 11 nm							
Calculation time t _{cal} Clock frequency	≤ 5 μs – ≤ 16 MHz							
Traversing speed ³⁾	≤ 600 m/min	1						
Interpolation error	±20 nm							
Electrical connection*	Cable (1 m or 3 15-pin D-sub co 4-pin MINI-SNA	m) with 8-pin M1 nnector (male) (fc P connector (male	2 coupling (ma or all interfaces e) (EnDat 3: E	ale) (for all ini s; EnDat 3: E3 30-R4)	terfaces; EnDa 30-RB), or	at 3: E30-RB),		
Cable length (with HEIDENHAIN cable)	≤ 100 m		≤ 50 m	≤ 30 m		≤ 50 m		
Supply voltage	DC 3.6 V to 14 \	/	1	1		1		
Power consumption ³⁾ (max.)	<i>At 3.6 V:</i> ≤ 700 mW <i>At 14 V:</i> ≤ 800 mW	At 3.6 V: ≤ 85 At 14 V: ≤ 95	0 mW 0 mW					
Current consumption (typical)	<i>At 5 V:</i> 75 mA (without load)	At 12 V: 35 mA (without load)	<i>At 5 V:</i> 95 m	A (without lo	ad)			
Vibration 55 Hz to 2000 Hz Shock 6 ms	\leq 500 m/s ² (El \leq 1000 m/s ² (El	N 60068-2-6) N 60068-2-27)						
Operating temperature	–10 °C to 70 °C							
Mass	Scanning head:≤ 18 g (without cable)Cable:M12 coupling and D-sub connector: 20 g/m; MINI-SNAP connector: 15 g/mConnectors:M12 coupling: 15 g; D-sub connector: 32 g; MINI-SNAP: 8 g							
 * Please select when ordering ²⁾ Mitsubishi: 1 nm: ML ≤ 2040 n Yaskawa: 1 nm: ML ≤ 1840 n 3) See General electrical information Product Information: LC 4100 	¹⁾ n = 1 f nm; 5 nm: nm; 5 nm: on in the <i>Interface</i>	or ML 3140 mm t ML \leq 10040 mm ML \leq 9040 mm; es of HEIDENHAI	to 5040 mm; r ; <i>IN Encoders</i> b	n = 2 for ML 10 nn 10 nn rochure	5140 mm to 7 n: ML ≤ 2004(n: ML ≤ 1804('040 mm; etc. [*] 0 mm 0 mm	*	

4



112 coupling (male) (for all interfaces; EnDat 3: E30-RB),	
for all interfaces; EnDat 3: E30-RB), or	
ale) (EnDat 3: E30-R4)	

LIC 4117, LIC 4137, LIC 4197

Absolute linear encoders for measuring lengths of up to 6 m

- · For measuring steps of down to 1 nm
- · Steel scale tape pulled through aluminum extrusions and fastened at center
- Consisting of a linear scale and scanning head (with straight or angled cable outlet)



Mounting options for scanning head



mm Tolerancing ISO 8015 ISO 2768:1989-mH ≤ 6 mm: ±0.2 mm





- \bigcirc = Beginning of measuring length (ML)
- ① = Carrier length

F = Machine guideway

- 1 = Optical centerline
- 2 = Mounting clearance between scanning head and extrusion
- 3 = Direction of motion of the scanning unit for ascending position values

ISO 7092-3

0 14.85

4

Rigid

Ø 3.7 mm > 8 mm ≥ 40 mm

Ø 2.9 mm > 6 mm ≥ 30 mm

ISO 4762–M3x (**a**+5)

R

configuration flexing

Frequent

а

D

d

// 0.25/25 D

2 0.15 +0.25

Scale	LIC 4007								
Measuring standard Coefficient of linear expansion*	Steel scale tape $\alpha_{therm} \approx 10 \cdot 10$	Steel scale tape with absolute and incremental METALLUR track $\alpha_{therm}\approx 10\cdot 10^{-6}~\text{K}^{-1}$							
Accuracy grade*	±3 µm (up to N	± 3 µm (up to ML 1040), ± 5 µm (for ML 1240 or greater), ± 15 µm $^{1)}$							
Baseline error	≤ ±0.750 µm/50	0 mm (typical)							
Measuring length (ML)* in mm	240 440 3040 3240 3 5840 6040	24044064084010401240144016401840204022402440264028403040324034403640384040404240444046404840504052405440564058406040							
Mass	Scale tape: 31 g	g/m; assembly pai	rts: 20 g; scale	e tape carrier:	: 68 g/m				
Scanning head	LIC 411	LIC 413	LIC 419F	LIC 419 M		LIC 419P	LIC 419Y		
Interface	EnDat 2.2	EnDat 3	Fanuc Serial Interface αi	Mitsubishi I interface	high speed	Panasonic Serial Interface	Yaskawa Serial Interface		
Ordering designation*	EnDat22	E30-RB E30-R4	Fanuc05	Mit03-4	Mit03-2	Pana02	YEC07		
Measuring step* ²⁾	10 nm, 5 nm, 1 nm 10 nm, 5 nm, 1 nm 10 nm, 5 nm, 1 nm								
Calculation time t _{cal} Clock frequency	≤ 5 µs ≤ 16 MHz	-	1						
Traversing speed ³⁾	≤ 600 m/min	1							
Interpolation error	±20 nm	±20 nm							
Electrical connection*	Cable (1 m or 3 m) with 8-pin M12 coupling (male) (for all interfaces; EnDat 3: E30-RB), 15-pin D-sub connector (male) (for all interfaces; EnDat 3: E30-RB), or 4-pin MINI-SNAP connector (male) (EnDat 3: E30-R4)								
Cable length (with HEIDENHAIN cable)	≤ 100 m		≤ 50 m	≤ 30 m		≤ 50 m			
Supply voltage	DC 3.6 V to 14 V	/	1	1					
Power consumption ³⁾ (max.)	$\begin{array}{llllllllllllllllllllllllllllllllllll$								
Current consumption (typical)	At 5 V: 75 mA (without load)	At 12 V: 35 mA (without load)	<i>At 5 V:</i> 95 m	A (without lo	ad)				
Vibration 55 Hz to 2000 Hz Shock 6 ms	\leq 500 m/s ² (El \leq 1000 m/s ² (El	N 60068-2-6) N 60068-2-27)							
Operating temperature	–10 °C to 70 °C								
Mass	Scanning head: Cable: Connectors:	≤ 18 g (withou M12 coupling M12 coupling:	it cable) <i>and D-sub col</i> 15 g; <i>D-sub c</i>	nnector: 20 g connector: 32	ı/m; <i>MINI-SNA</i> g; <i>MINI-SNA</i> ł	.P connector: 1 P: 8 g	5 g/m		

* Please select when ordering 1)

 $\pm 5\,\mu m$ after linear length-error compensation in the downstream electronics

²⁾ Mitsubishi: ML \leq 2040 mm / Yaskawa: ML \leq 1840 mm

³⁾ See General electrical information in the Interfaces of HEIDENHAIN Encoders brochure



LIC 4119, LIC 4139, LIC 4199

Absolute linear encoders for measuring lengths of up to 1 m

- For measuring steps of down to 1 nm
- Steel scale tape adhesively bonded to mounting surface
- Consisting of a linear scale and scanning head (with straight or angled cable outlet)







Mounting options for scanning head









d		R	l		
		Rigid	Frequent		
	con	ifiguration	flexing		
Ø 3.7 mm	>	8 mm	≥ 40 mm		
Ø 2.9 mm	>	6 mm	≥ 30 mm		

- F = Machine guideway
- * = Mounting error plus dynamic guideway error
- \bigcirc = Code start value: \ge 100 mm
- \bigcirc = Beginning of measuring length (ML)
- \bigcirc = Scale tape length
- 1 = Optical centerline
- 2 = Mounting clearance between scanning head and linear scale
- 3 = Direction of motion of the scanning unit for ascending position values

	LIC 400	9 ML 520 mm D 1230864-05 SN 1234	567891 VI	LIC 410	00 ENHAIN Bidenhain.de				
Scale	LIC 4009								
Measuring standard Coefficient of linear expansion*	Steel scale tape $\alpha_{\text{therm}} \approx 10 \cdot 10^{-10}$	Steel scale tape with absolute and incremental METALLUR track $x_{therm}\approx 10\cdot 10^{-6}~\text{K}^{-1}$							
Accuracy grade*	±3 μm, ±15 μm	±3 μm, ±15 μm ¹⁾							
Baseline error	≤ ±0.750 µm/50) mm (typical)							
Measuring length (ML)* in mm	70 120 1	70 220 270) 320 37	70 420 5	520 620	720 820	920 1020		
Mass	31 g/m								
Scanning head	LIC 411	LIC 413	LIC 419F	LIC 419M		LIC 419P	LIC 419Y		
Interface	EnDat 2.2	EnDat 3	Fanuc Serial Interface αi	Mitsubishi h interface	igh speed	Panasonic Serial Interface	Yaskawa Serial Interface		
Ordering designation*	EnDat22	E30-RB E30-R4	Fanuc05	Mit03-4	Mit03-2	Pana02	YEC07		
Measuring step ^{*2)}	10 nm, 5 nm, 1 nm	m, 1 nm 10 nm, 5 nm, 1 nm							
Calculation time t _{cal} Clock frequency	≤ 5 µs ≤ 16 MHz	-							
Traversing speed ³⁾	≤ 600 m/min								
Interpolation error	±20 nm								
Electrical connection*	Cable (1 m or 3 15-pin D-sub co 4-pin MINI-SNA	m) with 8-pin M1 nnector (male) (fc P connector (male	2 coupling (ma or all interfaces e) (EnDat 3: E	ale) (for all inte s; EnDat 3: E3 30-R4)	erfaces; EnDat 0-RB), or	t 3: E30-RB),			
Cable length (with HEIDENHAIN cable)	≤ 100 m ⁴⁾		≤ 50 m	≤ 30 m		≤ 50 m			
Supply voltage	DC 3.6 V to 14 V	/	I	I		1			
Power consumption ³⁾ (max.)	$\begin{array}{llllllllllllllllllllllllllllllllllll$								
Current consumption (typical)	At 5 V: 75 mA (without load)At 12 V: 35 mA (without load)At 5 V: 95 mA (without load)								
Vibration 55 Hz to 2000 Hz Shock 6 ms	$\leq 500 \text{ m/s}^2 \text{ (EN 60068-2-6)} \leq 1000 \text{ m/s}^2 \text{ (EN 60068-2-27)}$								
Operating temperature	-10 °C to 70 °C								
Mass	Scanning head: Cable: Connectors:	≤ 18 g (withou M12 coupling M12 coupling:	t cable) <i>and D-sub cor</i> 15 g; <i>D-sub c</i>	nnector: 20 g/i onnector: 32 g	m; <i>MINI-SNAI</i> g; <i>MINI-SNAP</i>	P connector: 1 2:8 g	5 g/m		

- * Please select when ordering
- ¹⁾ $\pm 5 \,\mu\text{m}$ after linear length-error compensation in the downstream electronics ²⁾ *Mitsubishi:* ML \leq 2040 mm / *Yaskawa:* ML \leq 1840 mm
- ³⁾ See General electrical information in the Interfaces of HEIDENHAIN Encoders brochure

11/2023

⁴⁾ With LIC 411 FS scanning head: clock frequency: 8 MHz

Product Information: LIC 4100

Electrical connection

EnDat 3 adapter cable and connecting cable (MINI-SNAP, E30-R4)

PUR $(2 \times 0.25 \text{ mm}^2) + (2 \times 0.09 \text{ mm}^2) \varnothing 5.$		
Adapter cable with 4-pin MINI-SNAP connector (female) and 15-pin D-sub connector (male)		1362192-xx
Connecting cable with 4-pin MINI-SNAP connector (female) and 4-pin MINI-SNAP connector (male)		1363049-xx

EnDat 3 pin layout

8-pin M12 coupling (E30-RB)			15-pin D-sub	connector (E	30-RB)	4-pin MINI-SNAP connector (E30-R4)			
						•			
	Power supply					Serial data t	ransmission		
► M12	8	2	5	1	3	4	7	6	
	4	12	2	10	5	13	8	15	
MINI-SNAP	1	-	3	-	-	-	2	4	
	U _P	Sensor U _P	0V •	Sensor 0 ∨	SD+_NEXT	SDNEXT	SD+	SD-	
	Brown/Green	Blue	White/Green	White	Gray	Pink	Violet	Yellow	

Cable shield connected to housing; U_P = Power supply voltage

Sensor: The sense line is connected in the encoder with the corresponding power line. Vacant pins or wires must not be used!

For information about connecting cables and pin layouts, please refer to the *Cables and Connectors* brochure.

